



Certificate No: MCS BBA 7071

Technology: MCS 012 – Pitched Roof Installation Kits

Products:
Marley SolarTile – Flashing Kits

Fusion Portrait flashing kits	
Components	Fusion portrait flashing kits for slates or tiles Solar outlet sealing collars specified by the Certificate holder Compatible with: Marley SolarTile xxx (Monocrystalline) Marley SolarTile xxxAG (Monocrystalline)
Installation Type	Roof-integrated
Permissible roof pitch (Angle °)	20° – 60°
Roofing substrate minimum requirements	Slated or tiled roofs
Maximum design wind uplift resistance (kPa) <i>Calculated by dividing the characteristic wind uplift resistance by the partial safety factor shown below.</i>	4.65
Partial (safety) factor	1
Fire classification to BS 476-3 : 2004	EXT.S.A.A The fire performance rating applies only to the roofing kit when used with the family of modules (family as referenced within MCS005) from which the tested module(s) came, or other modules that have identical material specification and design of: frame, coversheet, encapsulant, backing sheet and sealant.
Fire classification to CEN TS 1187 : 2012 Test 4	B _{Roof} (T4) The fire performance rating applies only to the roofing kit when used with the family of modules (family as referenced within MCS005) from which the tested module(s) came, or other modules that have identical material specification and design of: frame, coversheet, encapsulant, backing sheet and sealant.

Fusion Landscape flashing kits	
Components	Fusion landscape flashing kits for slates or tiles Solar outlet sealing collars specified by the Certificate holder Compatible with: Marley SolarTile xxx (Monocrystalline) Marley SolarTile xxxAG (Monocrystalline)
Installation Type	Roof-integrated
Permissible roof pitch (Angle °)	20° – 60°
Roofing substrate minimum requirements	Slated or tiled roofs
Maximum design wind uplift resistance (kPa) <i>Calculated by dividing the characteristic wind uplift resistance by the partial safety factor shown below.</i>	4.65
Partial (safety) factor	1
Fire classification to BS 476-3 : 2004	EXT.S.A.A The fire performance rating applies only to the roofing kit when used with the family of modules (family as referenced within MCS005) from which the tested module(s) came, or other modules

	that have identical material specification and design of: frame, coversheet, encapsulant, backing sheet and sealant.
Fire classification to GEN TS 1187 : 2012 Test 4	B _{Roof} (T4) The fire performance rating applies only to the roofing kit when used with the family of modules (family as referenced within MCS005) from which the tested module(s) came, or other modules that have identical material specification and design of: frame, coversheet, encapsulant, backing sheet and sealant.

Fusion flashing kits for sarking boards	
Components	Fusion flashing kits for slates or tiles Compatible with: Marley SolarTile xxx (Monocrystalline) Marley SolarTile xxxAG (Monocrystalline)
Installation Type	Roof-integrated
Permissible roof pitch (Angle °)	20° – 60°
Roofing substrate minimum requirements	Slated or tiled roofs Softwood sarking boards; 100 mm x 22 mm fitted with 3.35 x 65 mm nails Sarking board side bracket Sarking board twin panel joining bracket fitted with 4 x 50 mm screws (supplied)
Maximum design wind uplift resistance (kPa) <i>Calculated by dividing the characteristic wind uplift resistance by the partial safety factor shown below.</i>	4.65
Partial (safety) factor	1
Fire classification to BS 476-3 : 2004	EXT.S.A.A The fire performance rating applies only to the roofing kit when used with the family of modules (family as referenced within MCS005) from which the tested module(s) came, or other modules that have identical material specification and design of: frame, coversheet, encapsulant, backing sheet and sealant.
Fire classification to GEN TS 1187 : 2012 Test 4	B _{Roof} (T4) The fire performance rating applies only to the roofing kit when used with the family of modules (family as referenced within MCS005) from which the tested module(s) came, or other modules that have identical material specification and design of: frame, coversheet, encapsulant, backing sheet and sealant.

Marley Limited
Lichfield Road
Branston
Burton-on-Trent
DE14 3HD

The BBA (British Board of Agrément) has issued this Microgeneration Certification Scheme (MCS) Certificate to the company and products named above, in recognition of the products' compliance with the MCS Scheme Requirements for the technology named above.

On behalf of the British Board of Agrément

Date of Second issue: 12 December 2025



Hardy Giesler
Chief Executive Officer

The BBA is a UKAS-accredited product certification body (No. 0113). Certification is delivered under accreditation to BS EN ISO/IEC 17065. Readers MUST check the validity and latest issue number of this MCS Certificate by referring to the BBA website or contacting the BBA.

British Board of Agrément

1st Floor, Building 3, Hatters Lane
Croxley Park, Watford
Herts WD18 8YG

©2025

tel: 01923 665300
clientservices@bbacerts.co.uk
www.bbacerts.co.uk